| | |
|---|---|
| VOLTAGE | 0...300 V |
| CURRENT | 0...2000 mA |
| POWER | 0...300 W |
| PARAMETER RANGE | 1...100% of full scale |
| TIMER | 0...99:59 h |
| VOLT-HOURS | 0...99.99 kVh |
| DISPLAY | LCD, 2x16 characters |
| RESOLUTION | 1 V, 1 mA, 1 W |
| MEASUREMENT RESOLUTION | 1 V, 0.1 mA, 0.1 W |
| PROGRAMS | 9x9 set of parameters |
| OUTPUTS | 4 (4 mm sockets) |
| MINIMUM LOAD RESISTANCE | 5 Ω |
| NO LOAD DETECTION | Yes |
| GROUND LEAKAGE DETECTION | Yes |
| OVERLOAD DETECTION | Yes |
| COMPUTER CONTROL | Yes |
| PASSWORD PROTECTION | Yes |
| DATA-LOGGING | 3600 values |
| INTERVAL | 1...60 seconds |
| USB INTERFACE | Yes |
| AMBIENT TEMPERATURE | 0...40°C |
| RELATIVE HUMIDITY | 0...95%, non condensing |
| POWER REQUIREMENTS | 210...250 VAC, 50/60 Hz, 360 W 100...125 VAC, 50/60 Hz, 360 W |
| DIMENSIONS (WxDxH) | 31x26x13 cm |
| WEIGHT | 10 kg |