

	EV3150
VOLTAGE	0...1200 V
CURRENT	0...500 mA
POWER	0...300 W
PARAMETER RANGE	1...100% of full scale
TIMER	0...99:59 h
VOLT-HOURS	0...99.99 kWh
DISPLAY	LCD, 2x16 characters
RESOLUTION	1 V, 1 mA, 1 W
MEASUREMENT RESOLUTION	1 V, 0.1 mA, 0.1 W
PROGRAMS	9x9 set of parameters
OUTPUTS	4 (4 mm sockets)
MINIMUM LOAD RESISTANCE	70 Ω
NO LOAD DETECTION	Yes
GROUND LEAKAGE DETECTION	Yes
OVERLOAD DETECTION	Yes
COMPUTER CONTROL	Yes
PASSWORD PROTECTION	Yes
DATA-LOGGING	3600 values
INTERVAL	1...60 seconds
USB INTERFACE	Yes
AMBIENT TEMPERATURE	0...40°C
RELATIVE HUMIDITY	0...95%, non condensing
POWER REQUIREMENTS	210...250 VAC, 50/60 Hz, 360 W 100...125 VAC, 50/60 Hz, 360 W
DIMENSIONS (WxDxH)	31x26x13 cm
WEIGHT	10 kg